

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 August 2005 (18.08.2005)

PCT

(10) International Publication Number
WO 2005/074450 A3

(51) International Patent Classification⁷: **H01L 21/302**,
21/461, H05K 7/20, H05B 3/68

(21) International Application Number:
PCT/US2004/039780

(22) International Filing Date:
23 December 2004 (23.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/540,519 30 January 2004 (30.01.2004) US

(71) Applicant (for all designated States except US): **TOKYO ELECTRON LIMITED** [JP/JP]; 3-6, Akasaka 5-chome, Minato-ku, Tokyo 107-8481 (JP).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **HAMELIN, Thomas** [US/US]; 91 Central Street, Georgetown, MA 01833 (US).

(74) Agent: **MAIER, Gregory, J.**; Oblon, Spivak, McClelland, Maier & Neustadt, P.C., 1940 Duke Street, Alexandria, VA 22314 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:

— with international search report

(88) Date of publication of the international search report:
16 February 2006

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SUBSTRATE HOLDER HAVING A FLUID GAP AND METHOD OF FABRICATING THE SUBSTRATE HOLDER



(57) Abstract: A substrate holder (20) for supporting a substrate (30). A heating component (50) is positioned adjacent to a supporting surface and between the supporting surface and a cooling component (60). A fluid gap is positioned between the cooling component and the heating component, the fluid gap configured to receive a fluid to increase thermal conduction between the cooling component and the heating component. A brazing material is disposed between the cooling component and the heating component, the brazing material disposed adjacent to the fluid gap.

WO 2005/074450 A3